

## NORMA**QUICK**® S



# Efficient connection of fuel carrying lines in passenger and commercial vehicles




Leak-proof connection due to sealing with two O-rings



Cannot be opened under pressure due to two locking arms




Offers audible indicator to ensure locking





#### FLUID SYSTEMS & QUICK CONNECTORS





## **Applications**

NORMAQUICK® S connectors are ideal means for connecting fuel lines. They are designed to connect worldwide standardized spigots as per SAEJ2044 guidelines.

Material	
Housing:	PA12-GF50
Retainer:	PA12-GF30
O-rings:	Inside housing: FPM & FVMQ; on fir tree: FPM

Part number	Description	ØNW*	Designation (nec)
Part number	Description	MIN AA	Packaging quantity (pcs)
0715 6002 006	S NW 1/4" - 1/4" - 0°	1/4"	100
0715 6001 006	S NW 1/4" - 1/4" - 90°	1/4"	100
0715 6103 008	S NW 5/16" - 5/16" - 0°	5/16"	100
0715 6555 008	S NW 5/16" - 5/16" - 90°	5/16"	100
0715 6509 008	S NW 5/16" - 6 mm - 0°	5/16"	100
0715 6511 008	S NW 5/16" - 6 mm - 90°	5/16"	100
0715 6501 008	S NW 8 mm - 6 mm - 0°	8 mm	100
0715 6502 008	S NW 8 mm - 6 mm - 90°	8 mm	100
0715 6550 010	S NW 3/8" - 6 mm - 0°	3/8"	100
0715 6510 010	S NW 3/8" - 6 mm - 90°	3/8"	100
0715 6509 010	S NW 3/8" - 5/16" - 0°	3/8"	100
0715 6519 010	S NW 3/8" - 5/16" - 90°	3/8"	100
0715 6701 010	S NW 9.89 mm - 8 mm - 0°	9.89 mm	100
0715 6702 010	S NW 9.89 mm - 8 mm - 90°	9.89 mm	100
0715 6595 012	S NW 1/2" - 10 mm - 0°	1/2"	100
0715 6596 012	S NW 1/2" - 10 mm - 90°	1/2"	100
0715 6506 012	S NW 1/2" - 12 mm - 0°	1/2"	50
0715 6507 012	S NW 1/2" - 12 mm - 90°	1/2"	100
0715 6501 016	S NW 5/8" - 5/8" - 0°	5/8"	100
0715 6502 016	S NW 5/8" - 5/8" - 90°	5/8"	100
* NW (Nominal Width): Diameter of the connecting spigot			

#### More benefits

- ⊙ Compact design allows for assembly in narrow spaces



## NORMAQUICK® S is part of a broad portfolio. Discover more!





SR Single-Lock

Fuel Line Repair Kit

