
GN 162.1-NI


Bases for linear actuators













technical informations

Material

AISI CF-8 stainless steel NI, matte shot-blasted.

Clamping screws

Identification no. 2: with AISI 304 stainless steel-clamping screw DIN 912 and nut DIN 985.

Assembly

The standard clamping bolts are socket cap screws DIN 912, supplied assembled. They can be replaced by clamping kits GN 911 (description see table of dimensions).

Features and applications

Linear actuator connectors GN 162.1-NI are normally supplied only in connection with a mounted linear actuator and for function control.

By means of the clamping screw on the guide bore d_1 the movement can either be set or the linear actuator connector can be clamped (after setting of final adjustment).

Accessories

- Tubings <u>GN 990</u>. Linear actuators GN 291.
- Linear actuators GN 292.
 Clamping kits GN 911 (clamping handles GN 300.1 with distance bushing).

Standard Elements	Main dimensions								Clamping kits	Weigh			
Description	d ₁ Bore without slider bush	d _{1 Bore with slider bush}	d_2	d ₃	d_4	k	t	× ₁	x ₂	У ₁	У2	For d ₃	g
GN 162.1-G18-2-NI		G 18	5.5	M 6	M 3	40	7	50	38	50	38	GN 911-M6-22	190



STANDARD MACHINE ELEMENTS WORLDWIDE